



BNBM GROUP



Film Faced Plywood

www.bnbm.com.cn




Physical Properties

Modules of rupture	$\bar{x} \geq 24\text{MPa}, \bar{x} \geq 20\text{MPa}$
Modules of elasticity	$\bar{x} \geq 500\text{MPa}, \bar{x} \geq 14000\text{MPa}$
Moisture content	$\leq 12\%$
Bending	$\leq 1\%$
Thickness tolerance	$\pm 0.5\text{mm}$

Specification

Size	2440mm×1220mm
Thickness	10mm, 12mm, 15mm, 18mm

FORTUNE
500






BNBM GROUP



Bamboo Plywood

www.bnbnmg.com.cn



Physical Propertier

Modules of rupture	$\bar{x} \geq 40\text{MPa}$
Modules of elasticity	$\bar{x} \geq 4060\text{MPa}$
Moisture content	$\bar{x} \leq 10\%$
Absorbing water thickness expansion rate	$\bar{x} \leq 4\%$
Surface resistance	$\bar{x} \leq 600\text{mg}/100\text{r}$

Specification

Size	2440mm×1220mm
Thickness	8mm,9mm,10mm,12mm



Beijing New Building Material (Group) Co., Ltd.

Add: Building 4, Interwest Business Center, No.9, South Road

Shouti, Haidian District, Beijing, China

Tel: (86-10) 68799879

Fax: (86-10) 68799887

E-mail: lkf@bnbnmg.com.cn